



PRODUCT DATA SHEET

DuraGraphix Low Tack Adhesive Vinyl

Product Description: DuraGraphix™ water resistant ink jet coating on white calendared vinyl with low tack removable adhesive on a 90 lb. liner.

Suggested Uses: P.O.P., Signs, Banners, Prints, Posters, Decals

Product Code: DGRLT

Roll Dimensions:	Width (inches)	Length (feet)
On 2" cores unless noted.	24	50
	36	50
	42	50
	44	50
	50	50
	54	50

24" x 10' sample rolls or 8.5" x 11" sample sheets are available

Physical Properties:	Total Weight	306 g/m ²
	Thickness	12.3 mil with Liner Sheet / 6 mil without
	Opacity	95%
	Gloss @ 60°	2.8
	White Point	126
	Base	3.2 mil white vinyl on a 90 lb. liner with low tack removable clear adhesive
	Finish	Matte
	Water Resistant	Yes
	Application Temp.	Minimum 40° F
	Service Temp.	40° F to 200° F
	180° Peel Adhesion	½ hour – 14 ozs. PSTC-1 24 hour – 18 ozs. PSTC-1
	Lamination	Pressure Sensitive, Spray, Thermal, Liquid <i>For best results, please ensure that the print is encapsulated or the edge is sealed to prevent wicking into the print.</i>

Ink Compatibility: Pigment: Epson UltraChrome K3™, HP Vivera™, Canon LUCIA™, Eco-Solvent
For outdoor display, the use of pigment inks is recommended for fade and water resistance.

Printer Compatibility:	Epson	Canon imagePROGRAF
	7500 / 9500 / 7600 / 9600 / 10600 Epson Stylus Pro 3000 / 5000 / 7000 / 9000 / 10000 3800 / 4800 / 7800 / 9800 4880 / 7880 / 9880 / 11880 7900 / 9900	iPF6000S / iPF6100 / iPF6200 iPF8000S / iPF8100 iPF9000S / iPF9100
	HP	Mimaki
	DesignJet 5500	JV 4 Series
	DesignJet Z2100 / Z3100 / Z6100	Roland
	DesignJet Z3200	HiFi Jet FJ 52 / FJ 500 / FJ 540 / FJ 600

NOTE: This Product Data Sheet is intended to be used as a guideline only. Before using our print media, please verify that it is suitable for use with your printer. IJ Technologies will not assume liability for non-performance of the print media resulting from changes beyond our control in printing inks and/or printers.

Specifications are subject to change without notice. The product will be replaced if defective. No other liability will be accepted and all other warranties and conditions statutory, expressed or implied are excluded.